

ProCash 3000

Monofunction deposit system for banknote and document processing

In addition to its basic functions of cash and/or document processing and information processing on screen, the ProCash 3000 can be enhanced to meet the customer's specific needs:

- Print out receipts or other documents on the fully graphics-capable printer
- Enhanced editing function with an alphanumeric combi-keyboard
- Read barcodes
- Audio systems (loudspeakers/headset)

Features and highlights

- Frontload or rearload
- Standard PC technology
- Bundle deposit of up to 50 banknotes or documents
- LCD display (12.1" or 15") with autoscaling functionality
- Different installation versions with standard ready-made frames
- Certified EMV 2000 compliant
- Optical indicators at all input and output modules
- Optional: individual color scheme, labeling in Braille, energy-saving function



■ The ProCash 3000 provides a customer-friendly deposit function for banknotes and/or documents on a self-service system. Its compact form makes it ideal for a wide range of lobby installations in locations with high deposit frequencies.

ProCash 3000

TECHNICAL DATA

The new generation of deposit machines

Additional developments in the ProCash product family have bundled worldwide customer needs and trends. The flexibility that allows optimal configuration building and maximum system availability are unique in the market.

TECHNICAL DATA

SYSTEM CONTROL

Standard PC

DISPLAY

The autoscaling function is used to implement the different resolutions VGA, SVGA and XGA on a single display.

- 12.1" TFT LCD
- 15" TFT LCD

OPTIONAL

- Touchscreen
- Privacy display filter

Published by
Wincor Nixdorf International GmbH
Banking Division
Heinz-Nixdorf-Ring 1
D-33106 Paderborn
Germany
Phone +49 52 51 6 93 33 01
Fax +49 52 51 6 93 59 18
info.banking@wincor-nixdorf.com
www.wincor-nixdorf.com

© Wincor Nixdorf International GmbH
ProCash® is a registered trademark of Wincor Nixdorf International GmbH.
All rights, including rights created by patent grant or registration of a utility model or design, are reserved.
Delivery subject to availability, subject to change for technical reasons.

Order No. R10305-J-Z744-1-7600
Printed in Germany, June 2003

KEYPAD

- 8 stainless steel softkeys
- Numeric keypad including 4 function keys

OPTIONAL

- Encrypting PIN Pad (EPP)
- Keypad privacy shield
- Alphanumeric keyboard
- Braille labels

CARD HANDLING

- Hybrid card reader (motorized)
- Certified EMV 2000 compliant
- Tamper-proof card slot
- Card retained if not removed, returned if power fails

OPTIONAL

- DIP card reader
- Hybrid DIP card reader
- Various card retract boxes

CASH DEPOSIT

- 1 to 2 cassettes (standard delivery lead-sealable)
- Capacity of each cash cassette: 2000 banknotes
- No. of banknotes per bundle: 50
- Capacity of escrow: 50 banknotes
- Separate cassette for counterfeits

OPTIONAL

- Cassettes with lock

DOCUMENT PROCESSING

- Scanning module for bundled checks or deposit slips
- 1 to 2 cassettes (standard delivery lead-sealable)
- Cassette capacity: 2000 documents
- No. of documents per bundle: 50
- Capacity of escrow: 50 documents

OPTIONAL

- Cassettes with lock

SECURITY

SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV / VdS / LGAI

OPTIONAL

- Intruder alarm system
- Portrait camera
- Uninterruptible power supply

OPTIONS

PRINTER

- Receipt printer (pin or thermal)
- Journal printer (pin or thermal)

BARCODE READER

- Scans and processes barcodes in different formats

ADDITIONAL FEATURES

- Illuminated logo panel
- Info panel for card symbols
- Loudspeakers and/or headset connection

OPERATING SYSTEM

- Windows NT
- Windows XP

APPLICATION SOFTWARE

- ProTopas/Manger
- ProCash/PBM
- ProCash/(NDC (NCR Direct Connect))
- ProCash/DDC (Diebold Direct Connect)

POWER SUPPLY

110 - 120V~/220 - 240V~, 50-60 Hz

ENVIRONMENTAL CONDITIONS

Temperature: +5°C to +40°C
Rel. humidity: 5% to 85%

COMPLIANCE WITH STANDARDS

